

Product Information

micomRM125

125 Watt HF-SSB TRANSCEIVER 1.6 – 3.0 MHZ

The micomRM 125 is specifically designed to provide long-range radio communications for fixed or mobile base-stations. Complete with a 125 W transceiver in a 19 inch rack mount configuration, a, auto-sensing 110/220 VAC power supply, cooling fans and a multiple accessory interface junction box.

Meeting the world's strictest standards for radio equipment communication dependability, including MIL-STD-810, ALE per MIL-STD-188-141B Appendix A (JITC certified) and FED-STD-1045, the micomRM125 is the ideal solution for organizations whose operations require very reliable long-range radio communications for mission command and control.



Trans mitter (Cont.)

Hum & ripple-50 dB
Inband noise-60 dB (30 Hz BW)
Tx/Rx switching time10 msec
Tx tuning adjustmentsNone

OPTIONS

USB com port for external keyboard
PC control and programming package
PPS interface (internal/external pre-post selector)
Interface for secure voice device VP1 16
2 wire remote control panel

Mobat USA
1721 West Paul Dirac Drive
Tallahassee, FL 32310-3754
United States of America
Tel: 205-338-9888
Fax: 888-822-2891
E-mail: sales_US@mobat-usa.com
Web Site: www.mobat-usa.com